

Luminaire


Code M276125+M282100
Name Caelum 90 LED 2x30 - 4000K bianco + griglia

Measurem.

Code FTS1500269
Name Caelum 90 LED 2x30 - 4000K bianco + griglia

Luminaire Flux	1158.00 lm	Luminaire Power	28.00 W	Efficacy	41.36 lm/W	Efficiency	100.00%
Lamps Flux	1158.00 lm	Maximum value	1572.13 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	95 mm	Height	100 mm		
Round Luminous Area		Diam.	65 mm	Height	0 mm		
Horizontal Luminous Area		0.003318 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000803 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		09-02-2015		Maximum Gamma Angle		90	
Measurement Distance		0.00		Measurement Flux		1158.00 lm	
LED Flux=2970lm LED Power=25W Eff=39% EfcLed=119lm/W EfcLum=41lm/W Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	89 99 100 100 100			D DIN 5040		A60	
F UTE	1.00 A			B NBN		BZ 1	

Diam=95mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code M276125+M282100
Name Caelum 90 LED 2x30 - 4000K bianco + griglia

Measurem.


Code FTS1500269
Name Caelum 90 LED 2x30 - 4000K bianco + griglia

Luminaire Flux	1158.00 lm	Luminaire Power	28.00 W	Efficacy	41.36 lm/W	Efficiency	100.00%
Lamps Flux	1158.00 lm	Maximum value	1572.13 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	95 mm 65 mm	Height Height	100 mm 0 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.003318 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.000000 m2 0.000000 m2 0.000803 m2	
Coordinate system Date Measurement Distance		CG 09-02-2015 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 90 1158.00 lm	
LED Flux=2970lm LED Power=25W Eff=39% EfcLed=119lm/W EfcLum=41lm/W Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E. F UTE	89 99 100 1.00 A	100 100 100		D DIN 5040 B NBN	A60 BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.35	0.70	1.06	1.41	1.76	OC	0.35	0.70	1.06	1.41	1.76
OB	0.35	0.70	1.06	1.41	1.76	OD	0.35	0.70	1.06	1.41	1.76

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1820.53	1708.19	1147.86	683.96	355.78	131.82	37.45	4.53	1.64	0.19
OB	1820.53	1708.19	1147.86	683.96	355.78	131.82	37.45	4.53	1.64	0.19
OC	1820.53	1708.19	1147.86	683.96	355.78	131.82	37.45	4.53	1.64	0.19
OD	1820.53	1708.19	1147.86	683.96	355.78	131.82	37.45	4.53	1.64	0.19



H[m]	D[m]	Max lux	Med lux	Alpha=19.4°+19.4°	G=0.0
1.00	0.70	1821	1048		
2.00	1.41	455	262		
3.00	2.11	202	116		
4.00	2.82	114	65		
5.00	3.52	73	42		

Luminaire

Code M276125+M282100
Name Caelum 90 LED 2x30 - 4000K bianco + griglia

Measur.

Code FTS1500269
Name Caelum 90 LED 2x30 - 4000K bianco + griglia

Luminaire Flux	1158.00 lm	Luminaire Power	28.00 W	Efficacy	41.36 lm/W	Efficiency	100.00%
Lamps Flux	1158.00 lm	Maximum value	1572.13 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

UGR
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions	ViewedCrosswise					ViewedEndwise				
x=2H y=2H	21.5	22.2	21.7	22.4	22.6	21.5	22.2	21.7	22.4	22.6
x=2H y=3H	21.3	22.0	21.6	22.3	22.5	21.3	22.0	21.6	22.3	22.5
x=2H y=4H	21.3	21.9	21.6	22.2	22.4	21.3	21.9	21.6	22.2	22.4
x=2H y=6H	21.2	21.8	21.5	22.1	22.4	21.2	21.8	21.5	22.1	22.4
x=2H y=8H	21.2	21.7	21.5	22.0	22.3	21.2	21.7	21.5	22.0	22.3
x=2H y=12H	21.1	21.7	21.5	22.0	22.3	21.1	21.7	21.5	22.0	22.3
x=4H y=2H	21.3	22.0	21.6	22.2	22.5	21.3	22.0	21.6	22.2	22.5
x=4H y=3H	21.2	21.7	21.5	22.0	22.3	21.2	21.7	21.5	22.0	22.3
x=4H y=4H	21.1	21.6	21.5	21.9	22.3	21.1	21.6	21.5	21.9	22.3
x=4H y=6H	21.1	21.4	21.5	21.8	22.2	21.1	21.4	21.5	21.8	22.2
x=4H y=8H	21.0	21.4	21.4	21.7	22.1	21.0	21.4	21.4	21.7	22.1
x=4H y=12H	21.0	21.3	21.4	21.7	22.1	21.0	21.3	21.4	21.7	22.1
x=8H y=4H	21.0	21.4	21.4	21.7	22.1	21.0	21.4	21.4	21.7	22.1
x=8H y=6H	20.9	21.2	21.4	21.6	22.1	20.9	21.2	21.4	21.6	22.1
x=8H y=8H	20.9	21.1	21.4	21.6	22.0	20.9	21.1	21.4	21.6	22.0
x=8H y=12H	20.8	21.0	21.3	21.5	22.0	20.8	21.0	21.3	21.5	22.0
x=12H y=4H	21.0	21.3	21.4	21.7	22.1	21.0	21.3	21.4	21.7	22.1
x=12H y=6H	20.9	21.1	21.4	21.6	22.0	20.9	21.1	21.4	21.6	22.0
x=12H y=8H	20.8	21.0	21.3	21.5	22.0	20.8	21.0	21.3	21.5	22.0